

WESTERN PIPELINE PETROLEUM SPECIFICATIONS Effective : May 01, 2022	Units	Test Method	Low Sulphur Crude
Absolute Density at 15°C	kg/m ³	ASTM D5002	876-799
Vapour Pressure (VPCR₄ @ 37.8°C)	kPaa	ASTM D6377	May 1 to Oct 31 ◀85 Nov 1 to Apr 30 ◀95
Receipt Temperature	°C		40 (max.)
	°C		0.0 (min.)
Moisture and Contaminant Content ^{(1) (2)}	vol%	ASTM D4007	◀ 0.5
Colour		ASTM D1500	◀ 8.0
PH of Contained Water ⁽²⁾			▶ 5.0 & ◀7.0
Total Sulphur	wt%	ASTM D4294	◀ 0.5
Organic Chlorides in Whole Crude	wppm	ASTM D4929	◀ 1
Hydrogen Sulphide in the Liquid Phase	wppm	ASTM D5623	◀ 100 ⁽³⁾
Olefins, Total	wt%	H NMR	◀ 1
Phosphorous in Volatile Fraction	wppm	ICP AES D86 (250°C cut)	◀1.0
Total Salt	g/m ³		◀ 285
Viscosity @ 10.0 °C	cSt	ASTM D7042	◀20
NOTES:			
1. Contaminant content means all non-hydrocarbon materials excluding Nitrogen and Carbon Dioxide.			
2. No free water at -29°C.			
3. Guideline only.			
The symbol "◀" designates less than and "▶" designates greater than.			